

REMARKS

This is in response to the Office Action dated July 27, 2005. In view of the foregoing amendments and following representations, reconsideration is respectfully requested.

Initially, a substitute declaration is submitted herewith. The substitute declaration correctly identifies the filing date of the international application.

Next, the specification and abstract have been reviewed and revised. Due to the nature of the revision involved, a substitute specification and abstract (on a separate page) has been prepared. No new matter has been added. Also enclosed is a "marked-up" copy of the original specification and abstract to show the changes that have been incorporated into the substitute specification and abstract. The enclosed copy is entitled "Version with Markings to Show Changes Made."

Next, on page two of the Office Action, the drawings are objected to because the subject matter of claim 2 is not shown therein. Accordingly, claim 2 has been canceled, thereby obviating this objection.

Next, to facilitate the Examiner's reconsideration of the application, claims 1-21 have been canceled and replaced with new claims 22-29. Each of the new claims has been carefully drafted to ensure compliance with the requirements of 35 U.S.C. § 112, second paragraph, and to avoid the informalities noted by the Examiner on pages 2-3 of the Office Action. Thus, in view of the presentation of the new claims, it is submitted that the objections to the claims, and the rejections under 35 U.S.C. 112, second paragraph are now clearly obviated.

* * * *

Next, on pages 5-8 of the Office Action, the original claims are rejected as follows:

Claims 1-4, 6-9, 13-15, 17-19 and 21 are rejected under 35 U.S.C. 102(b) as being anticipated by Donecker et al. (U.S. Patent No. 3,772,454); and

Claims 5, 10-12, 16 and 20 are rejected under 35 U.S.C. 103(a) as being unpatentable over Donecker in view of Huetner (EP 577233).

It is submitted that the present invention, as embodied by the new claims, now clearly distinguishes over the Donecker and Huetner references for the following reasons.

The present invention, as defined in new Independent claim 22, is directed to a three-conductor cable having three intertwined electrical cables, and requires, *inter alia*, that each of the intertwined electrical cables includes:

- an inner conductor having a current lead formed of several intertwined wires;
- a neutral or return line formed by a number of component conductors that are distributed concentrically about the current lead;
- protective insulation disposed between the current lead and the component conductors of the neutral or return line; and
- a protective sheath surrounding the neutral or return line, wherein the protective insulation is approximately 0.2 to 1.4 mm thick.

Note that the limitation that specifies the thickness of the protective insulation (3) is supported in lines 23-24 of the specification as originally filed. Also, line 6 of page 4 describes that the inner conductor is formed of several intertwined wires.

Donecker discloses a torque balanced conductor cable 1 consisting of three strands, each having an insulated center core wire 4 surrounded by nine intermediate wires 6 and nine outer wires 8. Each center core wire 4 includes a core formed of a non ferrous

metal, such as copper or aluminum. Insulation 10 surrounds the center core wire 4 and extends into the interstices of the surrounding wires.

The Donecker cable is not a three-conductor cable as defined in claim 22. The Donecker cable is provided with only one conductor (4) in the center of each strand. In the explanation of the rejection, the Examiner characterizes the intermediate wires 6 as component conductors. However, the wires (6) are not conductors and are not insulated from each other. The wires 6 are uninsulated and not provided as component conductors, whereas in the present application, each conductor is insulated and therefore not in electrical contact with a neighboring conductor.

Note that wires 6, 8 are relatively rigid and stiff, and thus the Donecker cable would not be suitable for applications in which a flexible cable is required. The present invention provides a cable that can be used for flexible connections such as between UPS devices and data processing equipment (see page 6, lines 17-20).

Further, the Donecker cable is used for special applications as described in col. 1, lines 9-12 of the Donecker specification. This type of cable includes electrical conductors in the core surrounded by insulation and covered by one or more layers of steel wire. The Donecker cable is simply an improvement of this type of cable (see col. 1, lines 18-29).

Furthermore, claim 22 requires that each of the intertwined electrical cables has a protective sheath (8) surrounding the neutral or return line. In Donecker the outer sheath 32 is extruded over the three strands.

In view of the fact that Donecker lacks at least the component conductors, a current lead formed of intertwined wires, and protective insulation having a thickness of

approximately 0.2 to 1.4 mm; it is submitted that Donecker does not anticipate claim 22 or claim 29 under 35 U.S.C. 102(b).

Huttner is applied by the Examiner to teach a cable having an outer protective layer. However, Huttner does not disclose or suggest the features of claims 22 and 29 that are lacking in the Donecker reference. Therefore, it is submitted that claims 22 and 29 are clearly allowable of the collective teachings of the applied references.


In view of the above, it is submitted that the present application is now clearly in condition for allowance. The Examiner therefore is requested to pass this case to issue.

In the event that the Examiner has any comments or suggestions of a nature necessary to place this case in condition for allowance, then the Examiner is requested to contact Applicant's undersigned attorney by telephone to promptly resolve any remaining matters.

Respectfully submitted,

Christoph STUDER

By:



Michael S. Huppert
Registration No. 40,268
Attorney for Applicant

MSH/kjf
Washington, D.C. 20006-1021
Telephone (202) 721-8200
Facsimile (202) 721-8250
October 27, 2005

Version with Markings to
Show Changes Made

1

~~Three conductor cable~~
THREE CONDUCTOR CABLE

Technical domain

BACKGROUND OF THE INVENTION

1. Technical Field of the Invention

The invention concerns a three-conductor cable for power transmission at a frequency of at least 50 Hz, preferably at least 100 Hz, for example 400 Hz.

In the 400 Hz range, what are referred to as high-frequency power transmission cables are used. They are required for example on aircraft and ~~suchlike~~ the like, in order to connect them during stationary periods to a fixed network or a mobile power supply. Because the aircraft's on-board electronics are highly sensitive to current fluctuations, the cable must not generate any damaging asymmetrical voltage drops.

Another domain of application is engine technology. Thus, for example, high-frequency power transmission cables can also be used to power motors for spindle drives (induction/synchronous motors) or brushless DC motors.

State of the art

2. Description of the Related Art

Known high-frequency cables for frequencies of 400 Hz and above consist of four intertwined component conductors, consisting of three phase conductors and a neutral

2

and/or return line. In this construction, two phase conductors lie adjacent to the neutral and/or return line respectively. Between these two in turn lies the third phase conductor. This asymmetry results in a detrimental inductive voltage drop, which takes on great significance especially in cables which are used at the higher frequency range.

Asymmetrical electrical fields also arise due to the geometry of this known four-conductor cable, which can propagate interference to the immediate environment. The geometry of four stranded single-conductor cables also means that the mechanical position of the arrangement is not clearly defined, and this must normally be resolved by a central element.

However, there are also high-frequency power transmission cables with a symmetrical cable arrangement. These cables do not have the geometry-induced disadvantages of the aforementioned four-conductor cable. In these, the phase conductors run in pairs, stranded about the centrally-disposed neutral and/or return line. This creates a symmetrical arrangement with the neutral and/or return line in the ~~centre~~center and six phase conductors stranded symmetrically about this. In this arrangement, two opposing phase conductors are connected with each other. In this construction the return line takes up half the cross-section of the phase conductor. This is a disadvantage when there is an asymmetrical load, as often occurs with wide-body aircraft. Although in operational status the construction has relatively low inductance, it is expensive and usually fairly inflexible. It also requires insulation of two parallel three-phase systems, which means additional expense for high-quality insulation material. Moreover, with this cable the two associated

phase conductors must be combined before or inside the plug.

This second type of high-frequency power transmission cable ~~thus demonstrates the disadvantage of a~~ has the disadvantages of being complicated and relatively expensive manufacture. Furthermore these cables have a smaller surface over which the heat losses building up internally can be dissipated into the environment.

Summary of the invention

SUMMARY OF THE INVENTION

The invention is thus based on the problem of creating an electrical cable for power transmission at a frequency of at least 50 Hz and in particular a highfrequency power transmission cable which does not display the aforementioned disadvantages, whereby the latter especially should combine the advantages of a symmetrical arrangement with the flexibility and simplicity of twisted singleconductor construction and, with the same load capacity and operational safety, has a similar diameter to known four-conductor high-frequency cables.

~~This problem is solved according to the invention by a three-conductor cable with the characteristics of claim 1.~~

The three-conductor cable according to the present invention is intended, for example, for power transmission in the higher frequency range, from 400 Hz upwards, and

4

has a symmetrical construction of three intertwined electrical cables. Each of the three electrical cables is essentially ~~characterised~~ characterized in that it consists of a phase conductor, an insulation, and a concentrically-running neutral and/or return line. Embedded in the concentrically-running neutral and/or return line are dummy and control conductors, whereby an external protective sheath is additionally applied on top of these and the neutral and/or return line.

The three-conductor cable thus contains one concentric, external neutral and/or return line per phase conductor, which, however, in completely symmetrical operation practically never has to be used. Only a small inductance results from the geometrical structure, and this has a positive effect on the voltage drop.

~~Advantageous embodiments of the invention will be apparent from the dependent claims.~~

Brief description of the drawing

BRIEF DESCRIPTION OF THE DRAWINGS

Next, an embodiment of the invention will be described with the aid of the drawings, in which shows:

Figure 1: is a perspective view of an electrical cable; and

Figure 2: is a cross-section through a three-conductor cable according to the

invention with three intertwined electrical cables in accordance with Figure 1.

Description of a preferred embodiment

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

The electrical cable shown in Figure 1 separately and in Figure 2 intertwined with identical cables and referred to as a whole by the number 1 has a conductor-conductor, namely an inner conductor 2 with several intertwined wires.

The inner conductor 2 is encased by a protective sheath 3, preferably made of plastic, hereinafter also referred to as insulation.

Embedded in the concentrically-running neutral and/or return line, formed for example by eight component conductors 4, are dummy conductors 5 and control conductors 6 which for their part are coupled for control, monitoring, measurement and command purposes.

Over the component conductors 4 of the neutral and/or return line, the dummy conductors 5 and the control conductors 6 is applied a fleece band 7 and over that a protective sheath 8, which is preferably made from plastic.

The following details which relate to the diameter of the various layers are given by way of example and relate to an electrical cable which has an inner conductor cross-section of approx. 50 mm^2 and is intended for power transmission at a frequency of

6

400 Hz. Obviously with a larger current conductor cross-section or different frequency ranges, the various cross-sections can increase or decrease accordingly.

The protective sheath 3 surrounding the inner conductor 2 is some 0.2 to 1.4 mm thick and consists for example of a plastic band, for example made of polyester, which winds about the inner conductor 2 with an overlap of for example 20 to 30% of the band width, and also an extruded plastic layer.

Disposed around the insulation 3 are the neutral and/or return line, the control conductors 6 and the dummy conductors 5, symmetrically stranded. The eight component conductors 4 forming the return line consist for preference of Cu wires with a cross-section of some 2.5 mm² each.

The fleece band 7 is wound around the stranding consisting of the component conductors 4, the neutral and/or return line, the control conductors 6 and the dummy conductors 5, with an overlap of for example 20 to 30% of the band width, whereby this preferably has a wall thickness of some 0.05 to 0.2 mm.

The sheath 8 encasing the fleece band 7 consists of known material and has a wall thickness of for example 1.5 to 5 mm.

The three-conductor cable shown in Figure 2 and referred to as a whole as 10 has three intertwined electrical cables 1 of the aforementioned type. The three electrical cables

7

1, which are intertwined with each other can, in a special embodiment of the invention, however, additionally be held together by a sheath encasing them, for example in the form of a bandage or tube, which secures the electrical cables 1 against any axial displacement.

The three-conductor cable according to the invention has the advantages over the known high-frequency cables ~~described at the beginning in~~ that with the same load capacity, it has an absolutely symmetrical voltage drop on all three conductors, which proves smaller than in ordinary cables. At the same time, a smaller mechanical bending moment is achieved due to the construction according to the invention and thanks to the simple structure, the connection layout in the connection plug is simple to ~~realise~~ realize. Furthermore, no central dummy conductor in addition to the defined stranding is necessary, so that the cable thereby becomes lighter and more flexible.

Moreover, as the result of the construction according to the present invention, personal safety is increased. Before the phase conductor can be touched by being damaged with a metallic object, namely the neutral conductor carrying the earth potential must be damaged. The result of this is that in case of damage, the phase with the earth potential is short-circuited, before it can be touched live.

Compared with known four-conductor cables, the three-conductor cable has additional advantages such as a clear separation of control conductors and phase conductors, improved EMC ~~behaviour~~ behavior and more stable distribution. Compared with known cables with a symmetrical cable arrangement, the three-conductor cable

according to the present invention has the further advantage of improved heat radiation.

The three-conductor cable according to the present invention can be used in the frequency range of 50 Hz and over. Its symmetrical construction with relatively large cross-section of the return line offers optimal conditions for connections of asymmetrical loads. The symmetrical construction also offers striking advantages for flexible connections between UPS devices and data processing equipment, radar stations, and transmission equipment, inverter-motor connections with higher EMC requirements, etc.

It should be pointed out here that the electrical cable described with the aid of Figure 1 and also the three-conductor cable shown in Figure 2 represent only a selection of a number of potential embodiments of the invention and can be modified in various respects.

Thus for example there is the option of embedding the control conductors, not in the neutral and/or return line but in the respective phase conductor, as is the case in fact in known high-frequency cables. Also, the symmetrically distributed component conductors 4, instead of being stranded, can be disposed in meandering form about the phase conductor and the protective sheath 3 could consist of just one extruded plastic layer.

ABSTRACT

~~The present invention relates to a~~ A three-conductor cable (10) including ~~consisting of~~ three stranded electric cables (1), each ~~comprising~~ having a core that has a current conductor (2) and a neutral and/or return conductor. Each individual cable (1) is essentially ~~characterised~~ characterized in that the neutral and/or return conductor is configured from a number of individual conductors (4), distributed concentrically around the current conductor (2), that an insulating sheath (3) is provided between the current conductor (2) an the distributed individual conductors (4) of the neutral and/or return conductor and that a protective jacket covers the neutral and/or return conductor.